

Multimode 62.5 um Fiber Jumpers

SC-SC Fiber Jumpers

SC-LC Fiber Jumpers

LC-LC Fiber Jumpers

Features

- One-year warranty on all jumpers
- 3.00, 2.00, 1.8 mm Duplex Zipcord available. The 1.8 mm smaller cordage allows at least twice as many cables to be installed in a cabinet
- 100% of connectors tested for insertion loss and back reflection
- 100% of connectors visually inspected at 400x magnification
- Test results available upon request

Specifications

- Riser (OFNR), Plenum (OFNP), and Low Smoke-Zero Halogen (LSZH) rated cable jacket available
- Duplex 'zipcord' cable, jacket color Orange
- 62.5/125 um Fiber
- Minimum Bandwidth @ 850/1300 nm LED 200/500 MHz/km
- Serial 10 Gigabit Ethernet Distance 33 meters @ 850 nm
- Insertion Loss: 0.20dB typical / 0.35dB maximum
- Return Loss: -40dB typical / -25dB minimum
- Duplex Clips available
- Custom Cable lengths available

SC-SC (3mm)

SC-SC (2mm)

SC-LC (1.8mm)

LC-LC (1.8mm)

Ordering Information

Part No.:	Description
3, 2, 1.8 mm	
HRA026-SCD SCD-XXM	MM, DX, 3mm cable OFNR, SC to SC fiber jumper, XX meters long
2RA026-SCD SCD-XXM	MM, DX, 2mm cable OFNR, SC to SC fiber jumper, XX meters long
3ZH026-SCD SCD-XXM	MM, DX, 3mm cable LSZH, SC to SC fiber jumper, XX meters long
2ZH026-SCD SCD-XXM	MM, DX, 2mm cable LSZH, SC to SC fiber jumper, XX meters long
LMRA026-LCD SCD-XXM	MM, DX, 1.8mm cable OFNR, LC to SC fiber jumper, XX meters long
1.8ZH026-LCD SCD-XXM	MM, DX, 1.8mm cable LSZH, LC to SC fiber jumper, XX meters long
LMRA026-LCD LCD-XXM	MM, DX, 1.8mm cable OFNR, LC to LC fiber jumper, XX meters long
1.8ZH026-LCD LCD-XXM	MM, DX, 1.8mm cable LSZH, LC to LC fiber jumper, XX meters long

For Duplex Clips, add D to the SC.....Example: HRA026-SCD SCD-XXM



SC 3 mm Cable



LC to SC, 1.8 mm Cable



LC to LC, 1.8 mm Cable