

# Hybrid Adapters

## Components

## Overview

ARIA hybrid adapters provide connectivity between two different connector types.

ARIA hybrid adapters utilize reliable ferrule mating technology and ensure low insertion loss and return loss.

ARIA hybrid adapters offer superior performance and meet Telcordia GR-326-CORE requirements.



## Features

- JIS874-19
- JIS C5973
- TIA 568 Fiber Channel
- Telcordia GR326-CORE
- Performances are guaranteed

## Specifications

- Insertion Loss : 0.15 dB (SM)  
0.2 dB (MM typical)
- Temperature Range : -40C to +75C
- Durability: <0.2dB change after 500 cycles

## Part Numbers

Type	Sleeve	Keyway	Part Number
SC/ST Duplex	Phosphor Bronze	N/A	850-1000
SC/ST Duplex	Zirconia	N/A	850-2000
SC/ST	Zirconia	N/A	860-1000
SC/ST	Phosphor Bronze	N/A	860-2000
FC/SC	Zirconia	FC/APC key=2.0mm	860-3000
FC/SC	Phosphor Bronze	FC/APC key=2.0mm	860-4000
FC/SC	Zirconia	FC/APC key=2.2mm	860-3001
FC/SC	Phosphor Bronze	FC/APC key=2.2mm	860-4001
FC/SC	Zirconia	FC/APC key=2.4mm	860-3002
FC/SC	Phosphor Bronze	FC/APC key=2.4mm	860-4002
ST/FC	Zirconia	FC/PC key=2.2mm	860-5001
ST/FC	Phosphor Bronze	FC/PC key=2.2mm	860-6001
ST/FC	Zirconia	FC/PC key=2.4mm	860-5002
ST/FC	Phosphor Bronze	FC/PC key=2.4mm	860-6002